



Features/Applications

GREMFLEX® P-V0 is a UL94 V-0 compliant, halogen free, Polyester 0,25mm monofilament, expandable braided sleeve.
GREMFLEX® P-V0 offers a continuous working temperature of -50°C up to +150°C and outstanding flame retardant properties.
GREMFLEX® P-V0 is suitable for the protection of pipes, hoses and cable harnesses used for the mass transportation sector, where non flammable properties are required.

Various

Standard colours: Black with a three white tracers or Grey with a three black tracers.

Specifications

Compliant to V-0 (UL94).

Dimensions

Reference <i>GREMFLEX® P-V0</i>	Recommended range of use (mm)
003,0	01 to 04
004,0	02 to 06
005,0	03 to 07
006,0	04 to 09
008,0	05 to 11
010,0	07 to 14
012,0	08 to 16
015,0	10 to 20
020,0	14 to 25
025,0	18 to 30
030,0	20 to 42
040,0	30 to 54
050,0	40 to 66

Cutting

GREMFLEX® P-V0 can be cut to length.

Packaging

Available in spool, coils or cut pieces (on request).
Other packaging or diameter available upon request.

Property	Values	Test Methods
Physical	Working temperature	-50°C to +150°C
	Peak temperature	+175°C
	Melting point	+250°C
Flammability Smoke Toxicity	Self extinguishing	FMVSS 302
	Type B	D45 1333
	V-0 compliant	UL94 (Gremtek lab.)
	I2 - F1	NF F 16-101 & 102
	R22 & R23	NF EN 45545-2
	Halogen free	-
Chemical	Fluid resistance	Unaffected by most chemicals
		D47 1924



21/06/2021 Rev4

Whilst every attempt is made to provide data that is as accurate as possible the values provided should be treated as a guide only. It remains the responsibility of the user to test the product and determine suitability. GREMTEK shall not be held responsible for any loss or defect resulting from incorrect, improper or inappropriate use of this product.