



Features/Applications

GREMFLEX® PA11 is a self extinguishing, halogen free, Polyamide 11 0,30mm monofilament, expandable braided sleeve.
GREMFLEX® PA11 offers a continuous working temperature of -70°C up to +100°C, an outstanding abrasion resistance and a good expansion rate.
GREMFLEX® PA11 is suitable for the protection pipes, hoses and cable harnesses where high abrasion resistance is required.

Various

Standard colours: Black, grey.

Dimensions

Reference <i>GREMFLEX® PA11</i>	Recommended range of use (mm)
003,0	02 to 04
004,0	03 to 06
005,0	03 to 07
006,0	04 to 08
008,0	05 to 10
010,0	07 to 12
012,0	08 to 14
014,0	10 to 16
016,0	12 to 18
020,0	15 to 23
025,0	18 to 28
030,0	25 to 32
040,0	30 to 44
050,0	40 to 55
060,0	50 to 65

Cutting

GREMFLEX® PA11 can be cut to length.

Packaging

Available in spool, coils or cut pieces (on request).
Other packaging or diameter available upon request.

Property	Values	Test Methods	
Physical	Working temperature	-70°C to +100°C	
	Peak temperature	+150°C	
	Melting point	+185°C	
		Self extinguishing	FMVSS 302
	Flammability	Type B	D45 1333
	V-2	UL94 on compound	
Smoke toxicity	Halogen free	-	
Chemical	Fluid resistance	Unaffected by most chemicals	

