



Features/Applications

GREMFLEX® PA6.6 is a self extinguishing, halogen free, Polyamide 6.6 0,25mm monofilament, expandable braided sleeve.
GREMFLEX® PA6.6 offers a working temperature of -50°C up to +125°C, an outstanding abrasion resistance and a good expansion rate.
GREMFLEX® PA6.6 is suitable for the protection pipes, hoses and cable harnesses where high abrasion resistance is required.

Various

Standard colours: Black, grey, other colours available on request.

Dimensions

Reference <i>GREMFLEX® PA6.6</i>	Recommended range of use (mm)
003,0	02 to 04
004,0	03 to 06
005,0	03 to 07
006,0	04 to 08
008,0	05 to 10
010,0	07 to 12
012,0	08 to 14
014,0	10 to 16
016,0	12 to 18
020,0	15 to 23
025,0	18 to 28
030,0	25 to 32
040,0	30 to 44
050,0	40 to 55
060,0	50 to 65

Cutting

GREMFLEX® PA6.6 can be cut to length.

Packaging

Available in spool, coils or cut pieces (on request).
Other packaging or diameter available upon request.

Property	Values	Test Methods	
Physical	Working temperature	-50°C to +125°C	
	Peak temperature	+160°C	
	Melting point	+250°C	
		Self extinguishing	FMVSS 302
	Flammability	Type B	D45 1333
	Smoke	V-2	UL94 (Gremtek lab.)
	Toxicity	Halogen free	-
Abrasion resistance	CAT C	S21 5101 & D44 1959 PSA	
Chemical	Fluid resistance	Unaffected by most chemicals D47 1924	



Whilst every attempt is made to provide data that is as accurate as possible the values provided should be treated as a guide only. It remains the responsibility of the user to test the product and determine suitability. GREMTEK shall not be held responsible for any loss or defect resulting from incorrect, improper or inappropriate use of this product.