



Features/Applications

GREMFLEX® PET 025 is a self extinguishing, halogen free, Polyester 0,25mm monofilament, expandable braided sleeve.

GREMFLEX® PET 025 offers a continuous working temperatures of -50°C up to +150°C, an good abrasion resistance and a high expansion rate.

GREMFLEX® PET 025 is suitable for the protection of pipes, hoses and harnesses where abrasion resistance characteristics and color coding are required.

Various

Standard colours: Black, grey, orange, blue, red, green, other colours available on request.

Dimensions

Reference <i>GREMFLEX® PET 025</i>	Recommended range of use (mm)	Standard length (m/spool)
003,0	01 to 06	1000
006,0	03 to 09	1000
008,0	05 to 12	1000
010,0	07 to 17	1000
012,0	08 to 20	1000
015,0	10 to 27	1000
020,0	14 to 30	500
025,0	18 to 33	500
030,0	20 to 50	350
035,0	25 to 55	350
040,0	30 to 60	350
045,0	35 to 75	350
050,0	40 to 80	350

Cutting

GREMFLEX® PET 025 can be cut to length.

Packaging

Available in spool or cut pieces (on request).
Other packaging or diameter available upon request.

Property	Values	Test Methods	
Physical	Working temperature	-50°C to +150°C	
	Peak temperature	+175°C	
	Melting point	+250°C	
	Flammability	Self extinguishing	FMVSS 302
	Smoke toxicity	Halogen free	-
Chemical	Fluid resistance	Unaffected by most chemicals	

