



**Features/Applications**

GREMFLEX® PET H&L is a flexible, wrap-around, halogen free, Polyester monofilaments, braided sleeve with a hook-and-loop closure system.  
GREMFLEX® PET H&L offers a continuous working temperature of -50°C up to +150°C, a good resistance to abrasion and cut through as well as a heavy duty hook-and-loop closure.  
GREMFLEX® PET H&L is suitable for computer and electrical cables bundling applications which require easy on and off installation, rework and break outs.  
Used widely in the electrical construction business.

**Various**

Standard colours: Black, grey, white.



**Dimensions**

Reference <i>GREMFLEX® PET H&amp;L</i>	Recommended max. bundle diameter (mm)
013,0	8,0
019,0	12,0
032,0	20,0
051,0	32,0
064,0	40,0

**Cutting**

GREMFLEX® PET H&L can be cut to length.

**Packaging**

Available in spool, coils or cut pieces (on request).  
Other packaging or diameter available upon request.

Property	Values	Test Methods	
<b>Physical</b>	Working temperature	-50°C to +150°C	
	Peak temperature	+175°C	
	Melting point	+250°C	
	Flammability	Self extinguishing	FMVSS 302
	Smoke toxicity	Halogen free	-
<b>Chemical</b>	Fluid resistance	Unaffected by most chemicals	-
<b>Hook &amp; loop fastener</b>	Material	Polyamide 6.6	-
	Working temperature	-20°C à + 95°C	-
	Flammability	Non-flame retardant	-

