



Features/Applications

GREMFLEX® PET-L is a self extinguishing, halogen free, Polyester 0,22mm monofilament, expandable braided sleeve.
GREMFLEX® PET-L offers a continuous working temperature of -50°C up to +150°C and a very high expansion rate (ratio 3:1).
GREMFLEX® PET-L is suitable for the protection of cable harnesses where high expansion is required.

Various

Standard colours: Black, grey, other colours available on request.

Dimensions

Reference <i>GREMFLEX® PET-L</i>	Recommended range of use (mm)
003,0	03 to 08
006,0	05 to 12
012,0	08 to 21
020,0	12 to 30
030,0	18 to 55
040,0	24 to 66
050,0	30 to 82

Cutting

GREMFLEX® PET-L can be cut to length.

Packaging

Available in spool, coils or cut pieces (on request).
Other packaging or diameter available upon request.

Property	Values	Test Methods	
Physical	Working temperature	-50°C to +150°C	
	Peak temperature	+175°C	
	Melting point	+250°C	
		Self extinguishing	FMVSS 302
	Flammability	Type B	D45 1333
		V-2	UL94 on compound
Smoke toxicity	Halogen free	-	
Chemical	Fluid resistance	Unaffected by most chemicals	
		D47 1924	

