



**Features/Applications**

GREMFLEX® PPS-L is a self extinguishing, Polyphenylene Sulfide 0,25mm monofilament, expandable braided sleeve.  
GREMFLEX® PPS-L offers a continuous working temperature of -50°C up to +200°C, an excellent mechanical abrasion resistance as well as a low level of flammability and a high resistance to most automotive fluids.  
GREMFLEX® PPS-L is suitable for protecting cables, pipes and hoses situated within harsh environments. Used within the automotive, aerospace and military sectors.

**Various**

Product available upon request.  
Standard colours: Black, natural.

**Dimensions**

Reference GREMFLEX® PPS-L	Recommended range of use (mm)
003,2	02,4 to 06,4
006,4	03,2 to 09,5
009,5	04,7 to 15,9
012,7	06,4 to 19,1
015,9	09,5 to 25,4
019,1	12,7 to 31,8
031,8	19,1 to 44,5
044,5	31,8 to 69,8
050,8	38,1 to 76,2
063,5	44,5 to 92,0

**Cutting**

GREMFLEX® PPS-L can be cut to length.

**Packaging**

Available in spool, coils or cut pieces (on request).  
Other packaging or diameter available upon request.

Property	Values	Test Methods
<b>Physical</b>	Working temperature	-50°C to +200°C
	Peak temperature	+240°C
	Melting point	+250°C
	Flammability	Self extinguishing Type B
<b>Chemical</b>	Fluid resistance	Unaffected by most chemicals D47 1924

