

**Features/Applications**

GREMWRAP® PET 025 is a flexible, self-closing, halogen free, flame retardant, Polyester monofilament braided sleeve with an overlap.  
GREMWRAP® PET 025 offers a continuous working temperature of -50°C up to +150°C, a good wrapping strength, a high abrasion resistance and good noise dampening characteristics. It keeps its circular profile when bent and allows for quick and easy bundling of wires and cables.  
GREMWRAP® PET 025 is suitable for modular wire harness assemblies, cable bundling and for application where flame retardant properties are required.

**Various**

Standard colours: Black.

**Dimensions**

Reference <i>GREMWRAP® PET 025</i>	Recommended range of use (mm)
006,0	01 to 06
009,0	08 to 09
013,0	09 to 13
016,0	13 to 16
019,0	16 to 19
025,0	19 to 25
032,0	25 to 32
038,0	29 to 38
050,0	32 to 50

**Assembly tool**


GWtool available upon request. (4 sizes)

**Packaging**

Available in spool, coils.  
Other packaging or diameter available upon request.



GWtool



Sleeve shape

Property	Values	Test Methods	
<b>Physical</b>	Working temperature	-50°C to +150°C	
	Melting point	+240°C	
	Flammability	V2	UL94
	Toxicity	Halogen free	-
<b>Chemical</b>	Unaffected by most chemicals		



Recommandations for use:  
If GREMWRAP is to be used at 150°C or above (working temperature) please add tie-lock or tapes at a regular interval.

05/11/2019 Rev1

Whilst every attempt is made to provide data that is as accurate as possible the values provided should be treated as a guide only. It remains the responsibility of the user to test the product and determine suitability. GREMTEK shall not be held responsible for any loss or defect resulting from incorrect, improper or inappropriate use of this product.