



Features/Applications

GREMSEAL® GSSRS is a heat shrink solder termination sleeve made of an transparent irradiated heat shrink polyvinylidene fluoride tubing, a prefluxed solder perform and a meltable sealing inserts.

GREMSEAL® GSSRS offers a high resistance to abrasion, good insulation characteristics and outstanding encapsulation properties.

GREMSEAL® GSSRS is suitable for a wide variety of cable, pin-to-pin and wire-to-pin terminations.




Various

Standard colours: Tube colour is tint-blue transparent.

Dimensions

Reference <i>GREMSEAL® GSSRS</i>	As supplied (mm)		Wire Dimensions (mm)		Standard Color
	ØA (nom.)	Lenght L (max.)	ØB (min.)	ØC (min.)	
003,0	2,7 ±0,3	25,50	1,40	1,2	Blue
005,0	4,7 ±0,3	28,50	2,40	2	Blue
007,0	6,8 ±0,3	32,50	3,80	3,3	Blue
011,0	11,0 ±0,3	35,50	6,00	4,5	Blue
013,0	13,5 ±0,3	47,00	7,50	6	White
017,0	18,1 ±0,3	56,00	9,20	8	Blue
023,0	22,8 ±0,3	80,00	11,50	10	White



Scan to access
the last release!

Materials:

- Insulation sleeve: Heat shrinkable, radiation crosslinked, modified Polyvinylidene fluoride
- Meltable sealing rings: Thermally stabilized thermoplastic
- Solder preform: - Alloy: Sn/Bi

Recommended storage conditions: Keep in cool, dry, ventilated storage (maximum temperature of 35°C) and in closed container.

Property

	Values	Test Methods
Electrical Dielectric strength	2 kV/mm	ASTM D 2671

26/04/2024 Rev0

Whilst every attempt is made to provide data that is as accurate as possible the values provided should be treated as a guide only. It remains the responsibility of the user to test the product and determine suitability. GREMTEK shall not be held responsible for any loss or defect resulting from incorrect, improper or inappropriate use of this product.