



Features/Applications

GREMTUBE® GTP85 is a rigid, shiny, lay-flat, thin wall, PVC, heat shrink tubing. GREMTUBE® GTP85 offers good resistance to chemical fluids and good mechanical stiffness. GREMTUBE® GTP85 is suitable for packaging of electronic or electrical components and could replace paint coating on LV bus bars.

Various

Standard colours: Black, White, Clear.
Special colours are available on request.



Dimensions

These parts can be tailor-made to each customer's application.

- Flat width: 5 to 150 mm
- Thickness: 40 to 200 microns
- Finish: Shiny, matt or satin
- Spools as standard, cut pieces are available on request



Scan to access
the latest release!

Property		Values	Test Methods
Physical	Working temperature	-20°C to +85°C	-
	Longitudinal change	- 10% maxi	-
	Tensile strength	Unaged ≥ 63 MPa ≥ 120%	ISO 527-3
	Elongation at break		
	Flammability	Self-extinguishing	UL 94
	Density	1,35 g/cm ³	ISO 1183
Electrical	Dielectric strength	≥ 15 kV/mm	EN 60243
	Volume resistivity	6,5 x10 ¹² Ω.cm	IEC 62631

Recommended storage conditions: Keep in cool, dry, ventilated storage (maximum temperature of 25°C) and in closed container.

Whilst every attempt is made to provide data that is as accurate as possible the values provided should be treated as a guide only. It remains the responsibility of the user to test the product and determine suitability. GREMTEK shall not be held responsible for any loss or defect resulting from incorrect, improper or inappropriate use of this product.

20/08/2026 Rev4